

Thanks for trying our products! We know you'll love G2 quality and innovation.

Here is our full range of G2 products. To order or learn more, please log on at www.g2ergo.com.



Quick-Turn Throttle Tube
Opens faster than stock!



Billet Replacement Throttle Tube
2 piece design allows cam adjustability!



Competition Handguard System
Unique clamp design allows better cable routing!!



Nylon Bar End Mount Kit
Best handguard mounts...period!



Billet Grip Protector
Stop changing grips after every wipe-out!



Control Perch Spacer
Improved lever fit for big hands!

Quick-Turn Throttle Tube (Installation instructions)

- 1) Attach cam to tube with grip securely installed per manufacturer's recommendations. Slide tube/cam/grip assembly onto the right side of handlebar.
- 2) In fig. A, note hole position and size. Lower circular hole is for the "pull" cable, which opens the throttle. The upper, more oval shaped hole is for the "push" cable, which closes the throttle.
- 3) Insert "pull" throttle cable into correct hole (see Fig. B), then insert "push" throttle cable into remaining hole (see Fig. C). To determine how to properly match cables with holes on cam, see step "2".
- 4) Ensure proper positioning of cable guide when re-assembling throttle housing. **THIS IS ESPECIALLY IMPORTANT ON HONDA CRF MODELS !!** Improper guide location can cause restricted throttle movement and possibly stiction.
- 5) Align cables in plastic guides and assemble throttle housing. Torque bolts to manufacture's specification
- 6) Verify per manufacturer's specifications that all throttle components are assembled properly, such as example Fig. D. Adjust throttle cable free play, if necessary
- 7) With dead engine, twist throttle through full rotation to verify the throttle assembly turns freely and snaps back to "throttle off" position when rider's hand is released from grip. **DO NOT START ENGINE IF THROTTLE DOES NOT TURN FREELY. IMMEDIATELY DIS-ASSEMBLE THROTTLE ASSEMBLY AND GO TO STEP "3".**



Fig. A



Fig. B



Fig. C



Fig. D

G2 ERGONOMICS CORP WILL NOT BE RESPONSIBLE FOR IMPROPER INSTALLATION OR USAGE OF THIS PRODUCT. Please follow all instructions provided. If you are unsure of any installation procedure, please contact your local motorcycle dealer.

For more information, please logon to www.g2ergo.com, or see your local dealer.